

GUARD-F12 - EN50155 Certified Firewall/Router for Railway Applications

The new GUARD-F12 is a EN50155 Class Tx certified firewall/router. The GUARD-F12 has been developed specifically for the use in railway applications and is based on the robust GUARD-F1. The GUARD product line is designed and produced by MPL AG in Switzerland. The GUARD-F12 comes with 3 Fast Ethernet interfaces and M12 connectors, ideal for rugged industrial and railway applications.

Dättwil Switzerland, March 2013

The GUARD has specifically been designed for railways, industrial, and defense applications where security, quality, reliability, low power consumption, and long term availability are key. The GUARD-F12 is equipped with M12 connectors often used in railways applications. The housing comes in a small footprint and is available with DIN-Rail or Flange mounting and offers sufficient space to add other peripherals. The system can be customized for customer specific applications or uses.

The GUARD-F12 comes pre-installed with an adapted version of OpenWRT (www.openwrt.org). This Linux based embedded distribution provides all functionality required for operation as IPV4 and/or IPV6 firewall and router. Most of the configuration of the firmware installed can be done using a web based interface. For more specialized requirements, a console based configuration utility is available.



Highlights

The operating temperature range is from -20°C to +60°C and optionally even -40°C to +85°C without fan or case openings. The internal miniPCle slot allows various extensions (WLAN, GPRS...). Additionally available is an external USB connector and a microSD Memory Card slot for easy logging and/or configuration capabilities.

- Wide input voltage range (8 - 36VDC) with reverse polarity protection
- 3 Fast Ethernet ports with M12 connectors
- USB and SD interface (optional)
- Optional with 3 GigE ports

MPL's Railway Systems are EN50155 certified and undergo environmental testing to ensure reliable performance under a variety of conditions. For the climatic test, we have chosen the most severe test parameters from the Standard. The GUARD-F12 has been tested from -40°C to +85°C, called Tx in the EN 50155 Standard. It also includes the Railways Standard EMC and Mechanical tests. All required tests have been passed on the first go. Each GUARD delivered in extended temperature, will also be tested in our own climate chamber.

About the Company

MPL AG is located in Switzerland in the town of Daettwil near Zurich. It was founded 1985 by Rudolf Hug. Since 1985, MPL AG has been developing and manufacturing industrial computers (boards and systems) for industrial needs and industrial controls with a high quality standard. The success of the company is based on various unique solutions: a rugged, PC compatible industrial concept, long-term availability of our products, low power consumption, extended temperature range, and passive cooling concepts (fanless).

For further information, please visit - <http://www.mpl.ch>

contact information

Remy Lörtscher
MPL AG
Taefernstrasse 20
CH-5405 Dättwil, Switzerland
phone: +41 (0)56 483 34 34
sales@mpl.ch - www.mpl.ch

